





- (1) INLET GRILLE
- (2) 1 EA. 1" TWO-PLY POLYESTER SYNTHETIC 35% EFFICIENT PRE-FILTER PANEL
- (3) HIGH / OFF / LOW KEY SWITCH
- (4) 1 EA. MINIHELIC STATIC PRESSURE GAUGE
- (5) 1 BLOWER, PSC FORWARD CURVED, 1/5 HP, 115V 50/60 Hz, TWO SPEED, 3.2A (HIGH) 2.07A (LOW) THERMAL RESET PROTECTED, AIRFLOW 495 HIGH, 435 LOW
- (6) 1 EA. SIX (6) FOOT CORD, 18/3 CORD WITH 115V HOSPITAL GRADE PLUG
- (7) 4 EA. HEPA FILTER CUBE DRAW LATCHES
- (8) EXHAUST DUCT (6 X 9.875")
- (9) UNIT CONSTRUCTED OF 20 GA. STAINLESS TYPE 304, #4 FINISH
- (10) 1 EA. 12 X 12 X 11.5" HIGH CAPACITY HEPA FILTER RATED 99.99% ON 0.3 MICRON SIZE PARTICLES
- (11) ELECTRONIC RESETTABLE HOUR METER
- (12) 4 EA., 8 WATT UV (germicidal 253.4 nm) LAMPS

Notes: ELECTRICAL REQUIREMENTS: 115V, 1 ph, 60 Hz., 1.0 FLA, 5 AMP FUSE, ELECTRICAL WIRING IS IN ACCORDANCE WITH THE LATEST NEC STANDARDS

STANDARD	BIOLOGICAL 749 Hope Road Suite A Controls- Eatontown, NJ 07724  TITLE MICROCON EX-BUV-VE Vertical Exhaust (top)		
APPROVED BY	SCALE 1 ½" = 1'-1	O" DATE July 15, 2002 SH	EET